

Operating instructions (for shutter opening to two sides)

The following sequence tells you how to close the shutter starting with the shutter fully open and folded away inside the stacking areas.

1. Make sure that the shutter line is clear of people and obstacles.
2. Pull the shutter out of one of the stacking areas using the continuous grab handle.
3. Walk slowly to the opposite wall pulling the shutter along gently until the shutter is fully extended.
4. Pull the other shutter out of the stacking area on the opposite side of the opening and extend this shutter as in 3).
5. Once the two halves of the shutter are fully extended and touching each other slide one of the shutters backwards creating an opening of approximately 60cm and step inside the shop.
6. Return to one of the stacking areas and position the floor bolt closest to the stacking area into the respective floor socket. The floor bolt can be lowered by pulling the bolt release knob outwards while pushing the bolt down into the floor socket.
7. Let go of the knob only once the floor bolt is fully down. The bolt will be secured automatically in this position.
8. Walk along the shutter and position the remaining floor bolts into their respective floor sockets.
9. Repeat operations 7), 8) and 9) with the other half of the shutter.
10. Close the shutter by firmly engaging the locking posts with each other using the grab handle.
11. Once the locking posts are fully engaged the shutter can be locked by turning the key which activates the twin point hook lock.

The following sequence tells you how to open the shutter starting with the shutter fully closed and locked.

1. Unlock the shutter by turning the key, slide the shutter sideways and step inside the shop.
2. Raise the floor bolts (starting with the floor bolt nearest to the locking post) by pulling the release knob outwards and raising the bolt fully.
3. Make sure that the bolts are fully raised and only let go of the release knob once the bolt is in the highest possible position.

ATTENTION Moving the shutter while one or more floor bolts are not fully raised can cause damage to the shutter and to the floor.

4. Once all floor bolts have been raised and secured in the highest possible position the shutter can be moved by gently pushing the leader post while walking towards the stacking area.
5. Continue walking while pushing gently until the shutter is fully folded away into the stacking area.
6. Repeat operations 2), 3), 4) and 5) with the other half of the shutter.